



Features

LCD monitor; 19-inch, wide screen, panel mounted for cabinet or relay rack

Compact, 16-inch, space-saving keyboard and mouse with sliding tray

LCD mounting panel, 5.25-inch mounting rail, and rackmount hardware packages

1-year warranty

Basic Display

Avtec offers a basic display and keyboard solution for rackmount computers.

The DISP-BASIC model connects to one computer. This model includes a standard 19-inch LCD monitor, a sliding keyboard tray, a keyboard, and a mouse.

KEYBOARD SPECIFICATIONS

Size (H x W x D): 1 3/4 in x 16 in x 7 in x (44 mm x 405 mm x 180 mm)

Weight: 3 lbs (approximately 1.3 kg)

Color: Black

Cable Length: 1 1/10 yd (approximately 1.75 m)

Number of Buttons: 104 – US layout with Windows keys

Operating Temperature: 0°C to 60°C (32°F to 140°F)

Storage Temperature: –20°C to 60°C (–4°F to 140°F)

Current Consumption: Typ. 16 mA

Interface: PS/2 or USB

Compatibility: MS Windows XP, Windows 2000, XP embedded, Vista, Windows 10, Linux, Mac, UNIX, Sun

System Requirements: PS/2 – Plugs for keyboard and mouse, USB – USB plug and supporting operating system

Agency Approvals: FCC, CE, C-Tick, VDE, cURus

19-INCH MONITOR SPECIFICATIONS

Diagonal Size: 19 in

Type: TN LCD panel with LED backlight

Touch Technology: ACC-TSC-19-RES: Resistive, ACC-TSC-19-PC: Capacitive (single touch)

Brightness: 250 cd/m²

Contrast Ratio: 1000:1

Input Video Signal: ANALOG: 0.7 V_{p-p}/75 Ohms

Input: DVI-D and VGA 15 pin D-sub

Operating Altitude: 16404 ft / 5000 m

Operating Humidity: 20% to 80%

Operating Temperature: 41-95 °F / 5-35 °C

Pixel Pitch: 0.29 mm

Power Consumption: On: 12W Power saving mode: 0.3W

Resolution: 1280 x 1024

Storage Altitude: 40,000 ft (12,192m)

Storage Humidity: 10% to 85%

Storage Temperature: 14 °F to 140 °F (– 10 °C to 60 °C)

Sync: Separate Sync: TTL Level (positive/negative)

Synchronization Range (Automatic): Horizontal: 31.5 kHz to 81 kHz (analog/digital), Vertical: 56 Hz to 75 Hz

VESA Hole Configuration Spec.: 100 mm x 100 mm

Viewing Angle: 178° Vertical, 178° Horizontal

Voltage Rating: AC 100-120V/AC 220-240V

Response Time: Rapid Response (6 ms)

Compliant Standards: UL/C-UL or CSA, PCT (Gost), C-tck, SB-50 (California), FCC Class B/Canadian DOC, MPR II /MPR III, PSB, NOM, TUV GS, TUV Ergonomie, CE, GEEA/Energy label, SASO, ISO 9241-307, Pb free, RoHS, EPEAT Silver, Windows 7, Windows 10, Energy Star 8.0, and TCO 8.0 compliant

Weight With Stand: 8.4 lbs (3.8 kg)

Weight Without Stand: 7.5 lbs (3.4 kg)

Dimensions With Stand: 16.2 in x 15.9 in x 8.1 in (412.5 mm x 403.0 mm x 205.1 mm)

Dimensions Without Stand: 16.2 in x 13.4 in x 2.7 in (412.5 mm x 341.2 mm x 69.0 mm)